Louisiana State University Design Standards

DIVISION 12 - FURNISHINGS

1 WINDOW TREATMENTS

- 1.1 Blinds
 - 1.1.1 All blinds shall have a lifetime warranty on working mechanisms.
 - 1.1.2 Slat Requirements
 - 1.1.2.1 No smaller than .006 gauge will be accepted
 - 1.1.2.2 Only 25 millimeter or larger slat width will be accepted. Aluminum slats only no vinyl slats accepted.
 - 1.1.2.3 Spacing between slats shall be no greater than 21.5 millimeters
 - 1.1.3 Head rail metal thickness must be .025 gauge or greater
 - 1.1.4 Approved manufacturers are: Hunter Douglas-Dacor, Levalor-Riviera or equal (Prior approval by Planning, Design & Construction required for "equal").
- 1.2 Roller Shades
 - 1.2.1 All shades shall have a lifetime warranty on working mechanisms.
 - 1.2.2 Manually operated sunscreen roller shades with drive chain.
 - 1.2.2.1 Drive Chain: #10 qualified stainless steel chain rated to 90 lb. (41 kg) minimum breaking strength. Nickel plate chain shall not be accepted.
 - 1.2.3 Visually transparent single-fabric vinyl shade cloth.
 - 1.2.3.1 Maximum 5 percent open